



Specifications

Frequency 800 - 2000
 Power 500 Watts
 Isolation 5 dB
 Amplitude Imbalance ≤ 0.5 dB
 VSWR $\leq 1.5:1$

NO.	DESCRIPTION	REV	LTR	ECD NBR	DATE	ENG
1.	ADDED CONNECTOR DESCRIPTION .600 DIM WAS .500, ADDED MOUNTING HOLE DESCRIPTION		A		2/6/08	

CONNECTICUT
MICROWAVE
 CORPORATION
CHESHIRE, CT 06434

Connecticut Microwave Corp.
 1486 Highland Ave.
 Cheshire, Connecticut 06410

THIS DOCUMENT CONTAINS PROPRIETARY DATA OF THE CONNECTICUT MICROWAVE CORPORATION. NO DISCLOSURE, REPRODUCTION, OR USE OF ANY PART THEREOF MAY BE MADE EXCEPT BY WRITTEN PERMISSION.

HOLE	QTY	DESCRIPTION	ALL DIMENSION IN INCHES UNLESS OTHERWISE NOTED
A	.		XX ± .01, .XXX ± .005
B	.		ANGLES ± 1 DEG, FRACT ± 1/64
			ALL √ INDICATES 3.2 MICRONS
			MUST COMPLY WITH WORKMANSHIP STANDARDS SPEC

DRAWN BY		TITLE	
RR	RR	OUTLINE COMBINER	
DATE	10/6/05	8 WAY	
ENG		DWG NO. CM621.0001	
CHK		REV A	
PROJ			
MFG			
ENG			
SHEET	OF		